



C8 RPU	C4 RPU
C7 I/O	C3 CLOCK
C6 VPP	C2 RESET
C5 GND	C1 VCC
C1 VCC	C5 GND
C2 RESET	C6 VPP
C3 CLOCK	C7 I/O
C4 RPU	C8 RPU

JUMP	OPEN	SHORT
JP1 Fuse	Enable	Disable
JP2 Fuse	Enable	Disable
JP3 LED	Disable	Enable
JP4 LED	Disable	Enable
JP5 CD	Enable	Disable

LED	DESCRIPTION
D1	SCVCC
D2	AFMOR SCVCC

F1	Fuse
F2	Fuse
C1	0.1u
C2	0.1u
C3	0.01u
C4	12P
C5	12P
C6	12P
C7	0.01u
C8	12P
C9	12P
C10	12P
D1	LED
D2	LED

板厚介於0.684~0.836mm之間
建議板厚0.8mm

APPROVED:	- TOLERANCES -		UNIT:	TITLE :	SHEET
ENGINEER:	General	Angles	mm	AENEAS Smart Card Extender	1/1
CHECKED:	30~ ±0.25	0° ±3°	SCALE:	DRAWING NUMBER:	SIZE
DRAWN:	10~30 ±0.20	0.0° ±2°	1:1	A-R-SCE-PCBL	A4
Roger Tseng	5~10 ±0.15			Date	REV.
	0~5 ±0.10			2008/Jul/29th	A/0



Aeneas Electronics

背面