


USBM2

Wireless USB M.2(NGFF) Card Adapter

Product > M.2 interface > USBM2



First Impression

M.2 stands for Next Generation Form Factor which is invented for PCI-SIG by Intel and it is developed for flat and high-efficiency equipment such as Ultrabook™ or Tablet PCs. It is a natural transition from the Mini Card and Half Mini Card to a smaller form factor in both size and volume which supports multiple function add-in cards/modules including: Wi-Fi, Bluetooth, global navigation satellite systems, near field communication, Hybrid digital radio, wireless gigabit alliance (WiGig), wireless wide area network and solid-state storage devices. Also adds functionality to USB 3.0, display Port, SDIO and SSD-PCIe.

The USBM2 adapter is designed for desktop/Laptop PCs that convert 3G wireless M.2 Card to USB port. You can insert your M.2 card (Socket 2 SSIC-base WWAN) such as GSM, HSPA(3.5G), GPS, LTE cards to this adapter then plug to USB port through USB cable.

Standard SIM card Push connector is provided.

Function

- ◆ USB mini type-B connection to desktop or notebook PC
 - ◆ Supports system bus interface: USB (mini-B Connector)
 - ◆ Supports USB interface of M.2 Cards (Socket 2 SSIC-base WWAN) such as 2G GSM, GPRS, 3G,CDMA, WLAN,WWLAN, HSPA MODEM , GPS, 4G WiMAX, LTE, Mini Card to desktop PC.
 - ◆ Support SIM card Push Push connector.
 - ◆ Support [MHF4-RPSMA IPX 8cm cable](#)
 - ◆ Support [MHF4-SMA IPX 8cm cable](#) (Option)
 - ◆ DC Jack: External 5V Power Input
 - ◆ Support 3042 type M.2 card
 - ◆ Support Suspend Clock
- ◆ **Antenna Products (Click for [Bplus Antenna Comparison link](#)) :**
 - (Option) 800/1800 MHz Duck Antenna
 - (Option) 900/2100 MHz Duck Antenna
 - (Option) 2.4GHz MHz 2.15dBi Rubber Duck Antenna
 - (Option) 2.4/5.8GHz Rubber Duck Antenna
 - (Option) 5.8GHz 5dBi Rubber Duck Antenna
 - (Option) 2.3GHz 2.15dBi Rubber Duck Antenna
 - (Option) 2.5GHz 2dBi Rubber Duck Antenna
 - (Option) 3.5GHz 2.5dBi Rubber Duck Antenna

Specification

- ◆ M.2 Card to USB adapter.
- ◆ M.2 Specification Revision 0.9
- ◆ Universal Serial Bus Specification Revision 2.0
- ◆ 3042 type M.2 Card dimension.
- ◆ M.2 Mechanical Key: Key B
- ◆ SIM Connector for CDMA HSDPA/HSUPA,UMTS, GSM, GPRS, EDGE


System Requirements

- ◆ USB port
- ◆ Windows 2000, XP, Vista 32/64, Windows 7, Windows 8 or Linux

Notice:

USBM2 is M.2 (NGFF) passive adapter. Just only support Socket 2 SSIC-based WWAN M.2 Module (Key B).

USBM2 Package Contents



USBM2
 (Wireless USB M.2 Card Adapter) x1
 with [MHF4-RPSMA RF cable 8cm](#) x2



Y05-U04-060
 (USB 2.0 A Male to B Mini 5 Pin Cable 60cm) x1



Y05-U17-060
 (USB A Male to DC Power Cable) x1



Screwdriver x1



Flat-Head Screw x1